

Cover-PVC · Technical Data Sheet

Cover fabric in PVC-coated polyester

BASIC DATA

Property	Value	Test standard
Material	100% polyester, PVC-coated	ISO 2076
Weight	280 g/m²	-
Width	150 cm	-

TEST VALUES

Property	Value	Test standard
Waterproofness (water column)	4,000 mm	ISO 811
Maximum tensile strength (warp / weft)	1,214 / 751 N	ISO 13934-1
Tear strength (warp / weft)	57 / 43 N	ISO 13937-2
Seam slippage resistance (warp / weft)	465 / 382 N	ISO 13935-2
Abrasion resistance (Martindale)	60,000 cycles	ISO 12947
Lightfastness	Grade 7-8 (of 8)	ISO 105-B02
Colour fastness to rubbing dry / wet	Grade 4 / 4 (of 5)	ISO 105-X12

FINISH & CERTIFICATION

- UV-stabilised
- OEKO-TEX® Standard 100 certified
- 3-year warranty on waterproofness

COLOURS

Black · Anthracite · Dark blue · Dark brown · Dark green · Beige · Taupe

USE

Made to measure outdoor covers: garden furniture, lounges, tables, barbecues, hot tubs, equipment and machinery, winter protection for plants. Not an upholstery, awning or clothing fabric.

CARE



Do not machine wash



Hand wash up to 30 °C



Do not iron



Do not bleach



Do not tumble dry

Clean with lukewarm water, a sponge or soft brush and mild detergent, rinse with clear water and leave to air-dry.

All values are laboratory values of the fabric and describe the material, not the finished cover. Usual manufacturing tolerances apply.